mg - 10.60

3246 FILED NO. :

BOOK 3 PAGE 4

97 MAY 21 PM 1: 19

ACLLE HISSEL RECORDER COUNTY TOWN MORRISSEY SURVEYING, 1926 PAMMEL PARK ROAD, WINTERSET, IA 50273-8317, 515-462-2166 CORRECTED PLAT OF SURVEY CORRECTED NW 1/4, SEC. 3, T-76N, R-27W NE 1/4, SEC. 3, T-76N, R-27W SW 1/4, SEC. 3, T-76N, R-27W SE 1/4, SEC. 3, T-76N, R-27W MADISON COUNTY, IOWA CURVE\_DATA <u>CI</u> \$20.41,40°W-423.64 DELTA= 46°14'14" D= 14°15'00" L= 324 47 T= 171 65 R= 402 08 LC = 315 74 Ç2 NW 1/4 SE 1/4 DELTA= 46°14'14" D= 13"10'09" L= 351 10 T= 185 74 12'55°E 382 APPROX R= 435 08 SE COR 1/4, 1/4 SEC LINE ИW 1/4, N 35'12'55" E - 398.05 ŞEC 3 <u>C3</u> DELTA= 05°52'04" D= 04°45'38' LC=N 58°20'02" E L= 123 26 L.C.=N 58'20'02" E T= 61 69 341 65(C2) R= 1203 58 315.74(C1) LC = 123.21NE 1/4 SW 1/4 <u>C4</u> CENTERLINE MADISON CO HWY DELTA= 05°16'35" D= 04\*53'41' Ιġ L= 107 80 T= 53 94 R= 1170 58 969.19 8 12 LC = 107 76 Auditor's Parcel욄 <u>C</u>5 Letter-DDELTA- 00°39'00" 27.00 Acres D= 04°53'41' ,00° 0 L= 13 28 T**=** 664 R= 1170 58 LC = 13 28 81.27 S SOUTHERLY LINE MADISON CO HWY L.C =N 84°23'11" E L.C.=N 81'46'36" E - 13.28(C5) \_\_ 123 21(C3) SW. COR, L.C.=N 84'44'26" E - 107.76(C4) -33 02 NW. 1/4, N 04'44'36" W - 579.20 SEC 3 S 89°51'52" E - 1423 56 found 5/8" capped rebar, #10313 MONUMENTS I hereby certify that this plan, specification, plat, map, survey, or report was prepared by me or under my direct personal supervision and that I am a duly Licensed Professional Engineer and Land Surveyor under the laws of the State of Laws My Usagan papaged data is 12/21/97 ▲— found sec cor (plpe, stone, etc.) J BRIAN WORRISSEY 7995 set — 5/8" rebar with cap RLS 7995 Iowa. Yv license renewal date is 12/31/97 O- no monument found or set \_ Date <u>5/2//97</u> innimination of the found lot cor (pipe, stone, etc.) Brian Morrissey lowa Lic No 7995 SURVEY FOR AND OWNER MARVIN COX, 2432 OSAGE DR, WINTERSET, IA 50273

DATE OF SURVEY 3/13-17/97, 4/3-4/97 PROJ NO 180-973D

PAGE 1

MORRISSEY SURVEYING, 1926 PAMMEL PARK ROAD, WINTERSET, IA 50273-8317, 515-462-2166

CORRECTED

PLAT OF SURVEY

CORRECTED

NW 1/4, SEC. 3, T-76N, R-27W NE 1/4, SEC. 3, T-76N, R-27W SW 1/4, SEC. 3, T-76N, R-27W SE 1/4, SEC. 3, T-76N, R-27W MADISON COUNTY, IOWA

## DESCRIPTION -- PARCEL D

That part of the Northwest Quarter, the Northeast Quarter, the Southwest Quarter and the Southeast Quarter of Section 3, Township 76 North, Range 27 West of the Fifth Principal Meridian described as follows

Commencing at the southwest corner of the Northwest Quarter of saia Section 3, thence on an assumed bearing of South 89 degrees 51 minutes 52 seconds East along the south line of the Northwest Quarter of said Section 3 a distance of 1423 56 feet to the centerline of a Madison County Highway and the point of beginning,

thence northeasterly 13 28 feet along said centerline and a curve concave northwesterly and not tangent with the last described line, said curve has a radius of 1170 58 feet, a centra' angle of 00 degrees 39 minutes 00 seconds, and a chord 13.28 feet in length bearing North 81 degrees 46 minutes 36 seconds East,

thence North 81 degrees 27 minutes 09 seconds East along said centerline 969 19 feet, thence northeasterly 324 47 feet along said centerline and a tangential curve concave to the northwest and having a radius of 402 08 feet, a central angle of 46 degrees 14 minutes 14 seconds and a chord 315 74 feet in length bearing North 58 degrees 20 minutes 02 seconds East,

thence North 35 degrees 12 minutes 55 seconds East along said centerine 398 05 feet,

thence South 44 degrees 47 minutes 24 seconds East 647 03 feet, thence South 20 degrees 41 minutes 40 seconds West 423 64 feet, thence South 78 degrees 38 minutes 51 seconds West 1872 00 feet,

thence North 04 degrees 44 minutes 36 seconds West 579 20 feet to the centerline of a Madison County Highway

thence northeasterly 107 80 feet along said centerline and a curve concave northwesterly and not tangent with the last described line, said curve has a radius of 1170 58 feet, a central angle of 05 degrees 16 minutes 35 seconds, and a chord 107.76 feet in length bearing North 84 degrees 44 minutes 26 seconds East to the south line of the Northwest Quarter of said Section 3 and the point of beginning

Said tract contains 27 00 acres and is subject to a Madison County Highway Fasement over the northerly 138 acres thereof

## AREA BY 1/4, 1 4 SECTION

SE 1/4, NW 1/4= 273 ACRES(R O W = 087 AC) SW 1/4, NE 1/4= 687 ACRES(R O W = 035 AC) NF 1/4, SW 1/4= 1366 ACRES(ROW = 016 AC) NW 1/4, SE 1/4- 374 ACRES NW 1/4, SW 1/4= LESS THAN 0.01 ACRE

NOTE THIS PLAT OF SURVEY CORRECTS THE CURVE DATA OF CURVE C5 ON T E PLAT OF SURVEY RECORDED IN FARM PLAT BOOK 2, PAGES 790 AND 791



I hereby certify that this plan, specification, plat, map, survey, or report was prepared by me or under my direct personal supervision and that I am a duly Licensea Professional Engineer and Land Surveyor under the laws of the State of Iowa My license renewal dote is 12 31/97

- Date 5/21/97 Morriséey

SURVEY FOR AND OWNER. MARVIN COX, 2432 OSAGE DR, WINTERSET, IA 50273

PROJ NO 180-973D